



Single-track End carriages

Technical Parameters

Type	Length(m)	Power(kw)	Orbit(kg)	Gear diameter(Φ)	Output gear	Capacity(Ton)
T0.75-120	0.75	0.37	9	120	M3	1T
T1.2-150	1.2	0.37	9	150	M3	1.5T
T1.5-150	1.5	0.37	9	150	M3	2T
T2.0-180	2	0.37	12	160	M4	3T
T2.5-200	2.5	0.6	12	200	M4	5T
T2.0-250	2	0.6	15	250	M4	7.5T
T2.5-250	2.5	0.6	15	250	M4	7.5T
T3.0-250	3	0.6	15	250	M4	10T
T2.5-280	2.5	0.6	22	260	M5	10T
T3.0-280	3	1.5	22	260	M5	10T
T2.5-300	2.5	1.5-2.2	30	300	M5	15T
T3.0-300	3	1.5-2.2	30	300	M5	15T



Double-track power trolley

Size Specification for Electric Double-track Trolley

Type	Capacity(Ton)	Gear diameter(Φ)	Motor
PCT-200	2T	150-180	0.37*6P
PCT-300	3T	180	0.37*6P
PCT-500	5T	200	0.6*6P
PCT-750	7.5T	240	0.6*6P
PCT-1000	10T	280	0.6*6P
PCT-1600	16T	320	0.6*6P*2
PCT-2000	20T	380	0.37*6P*2